司聲企業股份有限公司

TONG SHEN ENTERPRISE CO., LTD.

MAILING ADD: P.O. BOX: 36-94, KAOHSIUNG, TAIWAN OFFICE ADD: NO.6, CHENG-AN ST., KAOHSIUNG, TAIWAN TEL: 886-7-642-0701 FAX: 886-7-642-0700

HTTP://www.tongshen.com.tw E-MAIL: tsound@ms19.hinet.net

Material Safety Data Sheet

Issue date: 18/MAR/2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product: Ethyl Cyanoacrylate Adhesive **Type:** W-50

Company address: Tong Shen Ent. Co., Ltd.

NO.6, CHENG-AN ST., KAOHSIUNG, TAIWAN

Region: TAIWAN Contact Information: Telephone: (886) 7-6420701

Emergency telephone: (886) 7-6420701

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components%ACGIHTLVOSHA PELOTHEREthyl Cyanoacrylate80-1000.2 ppm TWANoneNone7085-85-0

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

 Physical state: Liquid
 HEALTH:
 2

 Color:
 Clear Colorless
 FLAMMABILITY:
 2

 Odor:
 Sharp, Irritating
 PHYSICAL HAZARD:
 1

 Personal Protection:
 See Section 8

WARNING: MAY CAUSE EYE AND RESPIRATORY IRRITATION.

BONDS SKIN IN SECONDS.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Exposure to vapors above the established exposure limit results in respiratory irritation

which may lead to difficulty in breathing and tightness in the chest.

Skin contact: Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause

allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.

Eye contact: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth.

It is almost impossible to swallow.

Existing conditions aggravated by

exposure: Skin, eye, and respiratory disorders.

4. FIRST AID MEASURES

Inhalation: Remove to open space with fresh air. Seek medical attention to treat symptomatically if discomfort

persists.

Skin contact: Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a dull instrument.

If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel

or roll lips apart. Do not pull lips apart with direct opposing force.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are

bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond

同聲企業股份有限公司

TONG SHEN ENTERPRISE CO., LTD.

MAILING ADD: P.O. BOX: 36-94, KAOHSIUNG, TAIWAN OFFICE ADD: NO.6, CHENG-AN ST., KAOHSIUNG, TAIWAN TEL: 886-7-642-0701 FAX: 886-7-642-0700

HTTP://www.tongshen.com.tw E-MAIL: tsound@ms19.hinet.net

the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid

caused abrasive damage.

Ingestion: Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the

mouth making it almost impossible to swallow. Saliva will separate any solidified product in several

hours. Prevent the patient from swallowing any separated mass.

Notes to physician: Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded

tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they

should be treated symptomatically after adhesive is removed.

5. FIRE-FIGHTING MEASURES

Flash point: 80°C (176°F) to 93.4°C (200°F) Tagliabue closed cup

Autoignition temperature: 485°C (905°F)
Flammable/Explosive limits-lower %: Not determined
Flammable/Explosive limits-upper %: Not determined

Extinguishing media: Dry powder. Foam. Water spray. Carbon dioxide.

Special fire fighting procedures: Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Unusual fire or explosion hazards: None

Hazardous combustion products: Trace amounts of toxic and/or irritating fumes may be released and the use of

breathing apparatus is recommended.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Ventilate area.

Clean-up methods:

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

7. HANDLING AND STORAGE

Storage:

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after

handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly

closed until ready for use.

Incompatible products: No special restrictions on storage with other products.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA

regulations for respiratory use (29 CFR 1910.134).

Skin protection:Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.

Eye/face protection: Chemical splash goggles or safety glasses with side shields.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color:Clear ColorlessOdor:Sharp, IrritatingOdor Threshold:1-2 ppm

Vapor pressure: Less than 0.5 mm Hg at 25°C (77°F)

pH: Not applicable

Boiling point/range: Greater than 149°C (300°F)

Melting point/range:Not determinedSpecific gravity:1.04 at 20°CVapor density:Approximately 3Evaporation rate:Not available

Solubility in water: Polymerizes in presence of water

Partition coefficient (n-octanol/water): Not determined

VOC content: Less than 2%; 20 g/L (California SCAQMD Method 316B) (estimated)

企業股份有限

TONG SHEN ENTERPRISE CO.. LTD.

MAILING ADD: P.O. BOX: 36-94, KAOHSIUNG, TAIWAN OFFICE ADD: NO.6, CHENG-AN ST., KAOHSIUNG, TAIWAN

TEL: 886-7-642-0701 FAX: 886-7-642-0700

HTTP://www.tongshen.com.tw E-MAIL: tsound@ms19.hinet.net

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions

Hazardous polymerization: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

Hazardous decomposition products: None

Incompatability: Water, amines, alkalis and alcohols. Conditions to avoid: Spontaneous polymerization

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Acute oral LD50 >5000mg/kg (rat)(estimated). Acute dermal LD50 >2000mg/kg (rabbit)(estimated).

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA
Ethyl Cyanoacrylate 7085-85-0	No	No	No

Literature Referenced Target Organ & Other Health Effects

Health Effects Hazardous	Health Effects/Target Organs
Ethyl Cyanoacrylate 7085-85-0	Allergen, Irritant, Respiratory

12. ECOLOGICAL INFORMATION

Ecological information: Not known

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with Federal, State and local regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Combustible liquids, n.o.s. (Cyanoacrylate ester)

Hazard class or division: Combustible liquid

NA 1993 Identification number: Packing group: None

Exceptions: (Not more than 450 Liters) Unrestricted

Marine pollutant:

International Air Transportation (ICAO/IATA):

Proper shipping name: Aviation regulated liquids, n.o.s (Cyanoacrylate ester)

Hazard class or division: UN 3334 Identification number: Packing group: None

Exceptions: (Not more than 500ml) Unrestricted

WaterTransportation (IMO/IMDG):

Unrestricted Proper shipping name: Hazard class or division: None Identification number: None Packing group: None Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

All components are listed or are exempt from listing on the Toxic Substances TSCA 8 (b) Inventory Status:

Control Act Inventory.

TSCA 12 (b) Export Notification: **CERCLA/SARA Section 302 EHS:**

None. None. Immediate Health Hazard, Delayed Health Hazard, Fire, Reactive CERCLA/SARA Section 311/312:

CERCLA/SARA 313: None

No California Proposition 65 listed chemicals are known to be present. California Proposition 65: **Canada Regulatory Information**

All components are listed on or are exempt from listing on the Domestic CEPA DSL/NDSL Status:

Substances List.

WHMIS hazard class: B.3, D.2.B

同 聲 企 業 股 份 有 限 公 司 TONG SHEN ENTERPRISE CO., LTD.

MAILING ADD: P.O. BOX: 36-94, KAOHSIUNG, TAIWAN OFFICE ADD: NO.6, CHENG-AN ST., KAOHSIUNG, TAIWAN TEL: 886-7-642-0701 FAX: 886-7-642-0700

HTTP://www.tongshen.com.tw E-MAIL: tsound@ms19.hinet.net

16.OTHER INFORMATION

DISCLAIMER:

All the information of Material Safety Data Sheet is provided on the basis in good faith, and is believed to be trustworthy but is for reference only. Adhesion is very complicated and the result of it is much dependent on the surface material, additives, releasing agents of the substrates and user's methods. Tong Shen and its agents, dealers, distributors, directors and employees do not accept any liability for the results whatsoever arising from the use of Tong Shen's products due that the utilization of these products is simply out of Tong Shen's control. The users are responsible for selecting the suitability of the products and methods of use.